

## Cassini Round Technical Data



| Technical Data   |  |
|--|--|
| Net weight (kg)  | Cassini Round 60: 6.1kg / Cassini Round 80: 7.5kg  |
| Light Source   | LED  |
| Light Source Average Lifespan  | 30,000hrs - 50,000hrs  |
| Total Rated Wattage (W)  | Cassini Round 60: 45W / Cassini Round 80: 75W  |
| Lumens (Lm)  | Cassini Round 60: 3000lm / Cassini Round 80: 4560lm  |
| Kelvins (k)  | Cassini Round 60/80: 2700-6500K  |
| Is the mirror dimmable?  | No   |
| Energy Rating  | F  |
| Does the mirror require an earth connection?                             | No   |
| Can I bypass the sensor so the mirror comes on with the main room light? | No   |
| Colour temperature change (CTC) technology?                              | Yes  |
| What IP rating is the mirror?  | IP44 rated   |
| What orientation can the mirror be hung in?                              | N/A  |
| Is the heated pad only on when the miror is illuminated?                 | Yes  |
| How long is the warranty?  | 5 years from date of purchase on silvering coating on mirror<br>2 years from date of purchase on electrical components in the mirror |

## **Electrical Safety Information**

HiB recommends that all electrical bathroom products should only be fitted by a suitably qualified, Part P registered electrician in accordance with current IEE regulations.

Ensure mains power supply is switched off before starting installation.

Before drilling, ensure there are no hidden cables or pipes in the wall.

HiB recommend you receive the product before commencing with installation as all sizes and measurements are approximate. HiB try and ensure all measurements are as accurate as possible.

In the interest of continuous product development, HiB reserves the right to alter specification as necessary. E & OE.