

### **AMBOISE LUX MATT RECT 60X120**

REFERENCE	SIZE (cm)	THICKNESS (mm)	GROUP
A035775	60X120	9,10	PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES				
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments		
PHYSICAL PROPERTIES				
Water absorption capacity	EN ISO 10545-03	< 0,5%		
Flexion resistance	EN ISO 10545-04	=> 44 N/mm <sup>2</sup>		
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	Ш		
Thermal shock resistance	EN ISO 10545-09	It stands the test		
Cracking resistance	EN ISO 10545-11	It stands the test		
Frost resistance	EN ISO 10545-12	It stands the test		
CHEMICA	L PROPERTIES			
Resistance to acids	EN ISO 10545-13	GLA		
Resistance to alcalis	EN ISO 10545-13	GHA		
Resistance to cleaning products	EN ISO 10545-13	GA		
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GA		
Stains resistance	EN ISO 10545-14	5		







## **DECOR CATEDRA LUX MATT 60X120**

0,00

REFERENCE	
A036538	

SIZE (cm) 60X120

GROUP THICKNESS (mm) PC BIA GL



#### DIMENSIONS AND SURFACE PROPERTIES

**PHYSICAL PROPERTIES** 

EN ISO 10545-12

It stands the test

**CHEMICAL PROPERTIES** 





This document is commercial, with an informative nature relative to tested pieces. It cannot be used in legal or administrative proceedings, nor as an expert opinion or documentary proof. Images are not contractual.

Frost resistance



# ROD. AMBOISE LUX MATT 7,5X60

REFERENCE	SIZE (cm)	THICKNESS (mm)	GROUP	
A038288	7,5X60	9,70	PC BIA GL	5614

DIMENSIONS AND SURFACE PROPERTIES			
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	0.00	
PHYSICAL PROPERTIES			
Water absorption capacity	EN ISO 10545-03	0.00	
Flexion resistance	EN ISO 10545-04	0.00 <sup>2</sup>	
Thermal shock resistance	EN ISO 10545-09	0.00	
Cracking resistance	EN ISO 10545-11	0.00	
Frost resistance	EN ISO 10545-12	It stands the test	

CHEMICAL PROPERTIES			
Resistance to acids	EN ISO 10545-13	0.00	
Resistance to alcalis	EN ISO 10545-13	0.00	
Resistance to cleaning products	EN ISO 10545-13	0.00	
Resistance to chemical products in swimming pool water	EN ISO 10545-13	0.00	
Stains resistance	EN ISO 10545-14	0.00	







### AMBOISE LUX POL RECT 60X120

REFERENCE	SIZE (cm)	THICKNESS (mm)	GROUP
A035776	60X120	9,80	PC BIA GL



5

DIMENSIONS AND SURFACE PROPERTIES				
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplished all requeriments		
PHYSICAL F	ROPERTIES			
Water absorption capacity	EN ISO 10545-03	< 0,5%		
Flexion resistance	EN ISO 10545-04	=> 44 N/mm <sup>2</sup>		
Abrasion resistance (glazed Ceramic)	EN ISO10545-07	Ш		
Thermal shock resistance	EN ISO 10545-09	It stands the test		
Cracking resistance	EN ISO 10545-11	It stands the test		
Frost resistance	EN ISO 10545-12	It stands the test		
CHEMICAL F	PROPERTIES			
Resistance to acids	EN ISO 10545-13	GLA		
Resistance to alcalis	EN ISO 10545-13	GHB		
Resistance to cleaning products	EN ISO 10545-13	GA		
Resistance to chemical products in swimming pool water	EN ISO 10545-13	GA		

EN ISO 10545-14



Stains resistance





# **ROD. AMBOISE LUX POL 7,5X60**

REFERENCE	SIZE (cm)	THICKNESS (mm)	GROUP		
A038287	7,5X60	9,60	PC BIA GL	1 is a second of the	1

DIMENSIONS AND SURFACE PROPERTIES			
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	0.00	
PHYSICAL PROPERTIES			
Water absorption capacity	EN ISO 10545-03	0.00	
Elexion resistance	EN ISO 10545-04	0.00 <sup>2</sup>	
Thermal shock resistance	EN ISO 10545-09	0.00	
Cracking resistance	EN ISO 10545-11	0.00	
Frost resistance	EN ISO 10545-12	It stands the test	

CHEMICAL PROPERTIES			
EN ISO 10545-13	0.00		
EN ISO 10545-13	0.00		
EN ISO 10545-13	0.00		
EN ISO 10545-13	0.00		
EN ISO 10545-14	0.00		
	EN ISO 10545-13 EN ISO 10545-13 EN ISO 10545-13 EN ISO 10545-13		







### LAVABO DE PIE ROMA

REFERENCE	SIZE (cm)	THICKNESS (mm)	GROUP
A040867		0,00	PC BIA GL

#### **DIMENSIONS AND SURFACE PROPERTIES**

**PHYSICAL PROPERTIES** 

EN ISO 10545-12

It stands the test

**CHEMICAL PROPERTIES** 





Frost resistance